

# F-SERIES

## Specification Sheet

FVR 900



[www.isuzu.co.za](http://www.isuzu.co.za) f t

# ISUZU

*With you, for the long run*

MODEL	FVR 900
<b>AXLE LAYOUT</b>	4X2
<b>CONTROL</b>	FORWARD
MASS	
Permissible Body + Payload (kg)	10500
Tare - Total (T) (kg)	5500
Tare - Front (kg)	3300
Tare - Rear (kg)	2200
GVM (kg)	16000
V (kg)	16000
GCM (kg)	32000
D/T (kg)	32000
Axle - Front GA/GAU (kg)	7100
Axle - Front A/AU (kg)	7100
Axle - Rear GA/GAU (kg)	10500
Axle - Rear A/AU (kg)	9000
Litres of Fuel Tank 1 Included in Tare (litres)	15
Litres of Fuel Tank 2 Included in Tare (litres)	15
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes
<b>PERFORMANCE</b>	
Gradeability @ V (%)	38
Gradeability @ D/T (%)	19
Max. Geared Road Speed (km/h)	119
<b>MAJOR DIMENSIONS</b>	
Overall Length (mm)	10005
Overall Width (mm)	2400
Wheelbase (mm)	6050
CA - Cab to Bogie/Rear Axle (mm)	5424
CE - Cab to End of Chassis (mm)	7939
OH - Overall Height (mm)	2790
FOH - Front Overhang (mm)	1440
ROH - Rear Overhang (mm)	2515
Rear Axle Bogie Spacing (mm)	N/A
1/2 Rear Axle Bogie Spacing (mm)	N/A
EH - Chassis Rear End Height (mm)	1050
HH - Ground Clearance (mm)	245

MODEL	FVR 900
<b>AXLE LAYOUT</b>	4X2
<b>CONTROL</b>	FORWARD
MAJOR DIMENSIONS	
Chassis Width - Rear (mm)	850
Turning Radius - Curb to Curb (mm)	9750
Turning Radius - Wall to Wall (mm)	11366
<b>ENGINE</b>	
Make	Isuzu
Model	6HK1-TCS
Capacity (cm³)	7790
Layout	Diesel Inline 6
Type	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	206 @ 2400
Torque @ r/min (Nm)	882 @ 1450
Emissions Standard	Euro 2
<b>CLUTCH</b>	
Make	Exedy
Model	380
Type	Single
Diameter (mm)	380
Operation	Hydraulic Air-Assisted
<b>TRANSMISSION</b>	
Make	ZF
Model	9 S 1110
Type	Synchromesh
Shift	Manual Gearshift
No. of Gears Forward	9
First Gear Ratio : 1	9.48
Top Gear Ratio : 1	0.75
PTO (Power Take-Off)	Optional
<b>DRIVE AXLE</b>	
Make	Isuzu
Model Axle Front	R105
Model Drive Axle Rear	F071
Reduction Type	Single

MODEL	FVR 900
<b>AXLE LAYOUT</b>	4X2
<b>CONTROL</b>	FORWARD
DRIVE AXLE	
Final Ratio : 1	5.571
<b>SUSPENSION</b>	
Front	Multi-Leaf Springs
Rear	Multi-Leaf Springs
Shock Absorbers	Front
Stabilisers	Front & Rear
<b>STEERING</b>	
Operation	Power
<b>BRAKES</b>	
System Type	Full Air
Front	Drums
Rear	Drums
Anti-Lock Braking System (ABS)	Standard
Park / Emergency System	Spring
Exhaust Brake	Standard
Engine Brake	No
Retarder	No
<b>ELECTRICAL &amp; FUEL</b>	
Fuel Tank 1 Capacity (litres)	400
Fuel Tank 2 Capacity (litres)	0
<b>TYRES</b>	
Size & Ply Rating - Front	295 / 80 R22.5
Size & Ply Rating - Rear	295 / 80 R22.5
<b>CAB &amp; EXTRAS</b>	
Type	Medium
Roof	Low
No. of Bunks	0
No. of Seats	3
Air-Conditioning	Standard
Radio /CD	Standard
Tachograph	Optional
On-Board Computer	No
Tilt Cab	Yes

The information above is provided as a guide only. Specification is subject to change at any time. Please contact your nearest dealer to confirm current specification. Model/s shown may differ. E&OE. Date of print January 2018.