

N-SERIES

*Specification
Sheet*

NPR
24-SEATER BUS

www.isuzu.co.za f 

ISUZU

With you, for the long run

MODEL	NPR
DESCRIPTION	24-SEATER
ENGINE	
Engine & Exhaust Emission Level	4HK1-TCN Euro 2
Aspiration	Turbo & Intercooler
Injection System	Common Rail
Displacement (cm ³)	5193
Power @ r/min (kW)	110 @ 2600
Torque @ r/min (Nm)	404 @ 1500 – 2600
Transmission: Manual Synchronesh (NO AMT)	6-Speed MYY6S
Clutch Diameter (mm)	325 Single Plate
Axle Ratio : 1	4.556
Auxiliary Brake	Exhaust
ABS	Standard
Electrical System (V) & 2 X 12-V Batteries	24
Tyre Size	7.50 R16 12-Ply
Fuel Tank Capacity (litres)	100
Coolant Level Sensor	N/A
BEAME Tracking Device – Mix Telematics 2017	Standard
Road Speed (Max – Limited for Buses)	100
Gradeability % @ 'V' Mass, 1st Gear & Peak Torque	32
SEATING	
Driver	1
Passengers	24
Total	25
INTERIOR	
Individual Thin-Split Back Seat – Vinyl	Standard
Individual Thin-Split Back Seat – Printed Vinyl	Optional
Individual Thin-Split Back Seat – Dini Cloth	Optional
Basic Reclining Seats in Dini Cloth	Optional
Mechanical Suspension – Driver Seat	N/A
Air Suspension – Driver Seat	N/A

MODEL	NPR
DESCRIPTION	24-SEATER
INTERIOR	
Lap Belts – All Seats	Standard
Blue GRP Floor & Up to Window Height	Standard
GRP with LED Strip-Lights in Roof	Standard
Heater & Demister (Driver)	Standard
Parcel Shelf – Vinyl or Perforated Steel	Optional
EXTERIOR	
Tinted Windows – Rubber-Mounted Sides Only	Standard
Tinted Bonded Side Windows	Optional
Windscreen 1-Piece Panoramic (Curved)	Standard
Windscreen 2-Piece Panoramic (Shaded Top)	N/A
Windscreen 2-Piece Flat Front	N/A
Door Entrance Position In	Wheelbase
Driver Door	Standard
OTHER SPECIFICATIONS	
Standard Exterior Colour – White	Standard
Sunvisor – Driver	Standard
Radio/CD, with USB Port, Speakers & Antennae	Optional
Towbar & 50 mm Ball Hitch & 7-Pin Electrics	Optional
Lockers – Side in Wheelbase (Build to Order)	1 X 0.4 m ³
Lockers – Rear Overhang (Build to Order)	2 X 0.4 m ³ , 1 X LHS & 1 X RHS
DIMENSIONS	
Wheelbase (mm)	3815
Overall Length (mm)	7427
Overall Height (mm)	2860
Overall Width (mm)	2240
Rear Overhang (mm)	2349
Front Overhang (mm)	1263
Ground Clearance in Wheelbase (mm)	400

MODEL	NPR
DESCRIPTION	24-SEATER
ANGLES	
Approach Angle (°)	18
Departure Angle (°)	12
MASS (kg)	
Tare – Front (Estimated)	2100
Tare – Rear (Estimated)	3000
Tare – Total (Estimated)	5100
V – Rating	7500
D/T – Rating	11000
A – Front	2900
A – Rear	5600
STANDARD EQUIPMENT	
Tools & Tool Box	Standard
Mudflaps on all Wheels	Standard
Spare Wheel, Carrier & Winch	Standard
Swing-Out Battery Box (2 X 12-V Batteries)	Standard
Lockable Slam-Type Passenger Door	Standard
Roof Vent / Escape Hatch	Standard
Emergency Exits – Windows & Roof Vent	Standard
2.5 kg Fire Extinguisher	Standard
Front Tow Hook	Standard
Front & Rear Bumper	Standard
Lockable Fuel Cap (Uses Ignition key)	Standard
Number Plate Holders (Front & Rear)	Standard
Exhaust Pipe Modified to Extend Beyond Body	Standard
Reverse Buzzer	Standard
WARRANTY & SERVICE	
Warranty – Chassis	2 Years / Unlimited km
Warranty – Bus Main Body (Integrity & Structure)	3 Years
Service Intervals (Standard Operation)	20 000 km
Defective Bus Component: Hinges, Locks, etc.	1 Year