

N-SERIES

Specification Sheet

NPR 400 CREW AMT



www.isuzu.co.za f t

ISUZU

With you, for the long run

MODEL	NPR 400 CREW AMT
AXLE LAYOUT	4X2
CONTROL	FORWARD
MASS	
Permissible Body + Payload (kg)	4600
Tare - Total (T) (kg)	2900
Tare - Front (kg)	1900
Tare - Rear (kg)	1000
GVM (kg)	7500
V (kg)	7500
GCM (kg)	11000
D/T (kg)	11000
Axle - Front GA/GAU (kg)	3100
Axle - Front A/AU (kg)	2900
Axle - Rear GA/GAU (kg)	6600
Axle - Rear A/AU (kg)	5600
Litres of Fuel Tank 1 Included in Tare (litres)	15
Litres of Fuel Tank 2 Included in Tare (litres)	0
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes
PERFORMANCE	
Gradeability at V (%)	32
Gradeability at D/T (%)	22
Max. Geared Road Speed (km/h)	116
MAJOR DIMENSIONS	
OL - Overall Length (mm)	6635
OW - Overall Width (mm)	1995
WB - Wheelbase (mm)	3815
CA - Cab to Bogie/Rear Axle (mm)	2241
CE - Cab to End of Chassis (mm)	3961
OH - Overall Height (mm)	2270
FOH - Front Overhang (mm)	1110
ROH - Rear Overhang (mm)	1710
EH - Chassis Rear End Height (mm)	845
HH - Ground Clearance (mm)	195

MODEL	NPR 400 CREW AMT
AXLE LAYOUT	4X2
CONTROL	FORWARD
MAJOR DIMENSIONS	
Chassis Width - Rear (mm)	845
Turning Radius - Curb to Curb (mm)	7150
Turning Radius - Wall to Wall (mm)	7900
ENGINE	
Make	Isuzu
Model	4HK1-TCN
Capacity (cm ³)	5193
Layout	Diesel Inline 4
Type	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	110 @ 2600
Torque @ r/min (Nm)	404 @ 1500 - 2600
Emissions Standard	Euro 3
CLUTCH	
Make	N/A
Model	N/A
Type	N/A
Diameter (mm)	N/A
Operation	Automated Hydraulic-Controlled Wet Clutch
TRANSMISSION	
Make	Isuzu
Model	MYY6S (AMT)
Type	6-Speed Synchronmesh
Shift	Automated Manual
No. of Gears Forward	6
First Gear Ratio : 1	5.979
Top Gear Ratio : 1	0.759
Transfer Case	No
PTO (Power Take-Off)	Optional
DRIVE AXLE	
Make	Isuzu
Model Axle Front	F031

MODEL	NPR 400 CREW AMT
AXLE LAYOUT	4X2
CONTROL	FORWARD
DRIVE AXLE	
Model Drive Axle Rear	R066
Reduction Type	Single
Final Ratio : 1	4.556
SUSPENSION	
Front	Semi-Elliptic Springs
Rear	Semi-Elliptic Springs
Shock Absorbers	Front & Rear
Stabilisers	Yes
STEERING	
Operation	Power
BRAKES	
System Type	Hydraulic Brake Boost
Front	Drums
Rear	Drums
Anti-Lock Braking System (ABS)	Standard
Park / Emergency System	Drum on Propshaft
Exhaust Brake	Standard
ELECTRICAL & FUEL	
Fuel Tank 1 Capacity (litres)	100
Fuel Tank 2 Capacity (litres)	0
TYRES	
Size & Ply Rating - Front	7.50 R16-12PR (215 / 75 R17.5)
Size & Ply Rating - Rear	7.50 R16-12PR (215 / 75 R17.5)
CAB & EXTRAS	
Type	Crew
Roof	Low
No. of Bunks	0
No. of Seats (Lap Rear & Centre)	7
Air-Conditioning	Optional
Radio	Optional
Tilt Cab	No

The information above is provided as a guide only. Specification is subject to change at any time. Please contact your nearest dealer to confirm current specification. Model/s shown may differ. E&OE. Date of print January 2018.