

F-SERIES

*Specification
Sheet*

FVR
65-SEATER BUS

www.isuzu.co.za f 

ISUZU

With you, for the long run

MODEL	FVR
DESCRIPTION	65-SEATER
ENGINE	
Engine & Exhaust Emission Level	6HK1-TCS Euro 2
Aspiration	Turbo & Intercooler
Injection System	Common Rail
Displacement (cm ³)	7790
Power @ r/min (kW)	206 @ 2400
Torque @ r/min (Nm)	882 @ 1450
Transmission: Manual Synchromesh (NO AMT)	9-Speed ZF 9 S 1110
Clutch Diameter (mm)	380 Single Plate
Axle Ratio : 1	5.571
Auxiliary Brake	Exhaust
ABS	Standard
Electrical System (V) & 2 X 12-V Batteries	24
Tyre Size	295 / 80 R22.5 16-Ply
Fuel Tank Capacity (litres)	1 X 400
Coolant Level Sensor	Standard
BEAME Tracking Device – Mix Telematics 2017	Standard
Road Speed (Max – Limited for Buses)	100
Gradeability % @ 'V' Mass, 1st Gear & Peak Torque	38
SEATING	
Driver	1
Passengers	65
Total	66
INTERIOR	
Individual Thin-Split Back Seat – Vinyl	Standard
Individual Thin-Split Back Seat – Printed Vinyl	Optional
Individual Thin-Split Back Seat – Dini Cloth	Optional
Basic Reclining Seats in Dini Cloth	Optional
Mechanical Suspension – Driver Seat	N/A
Air Suspension – Driver Seat	Standard

MODEL	FVR
DESCRIPTION	65-SEATER
INTERIOR	
Lap Belts – All Seats	Optional
Blue GRP Floor & Up to Window Height	Standard
GRP with LED Strip-Lights in Roof	Standard
Heater & Demister (Driver)	Standard
Parcel Shelf – Vinyl or Perforated Steel	Optional
EXTERIOR	
Tinted Windows – Rubber-Mounted Sides Only	Standard
Tinted Bonded Side Windows	Optional
Windscreen 1-Piece Panoramic (Curved)	N/A
Windscreen 2-Piece Panoramic (Shaded Top)	Standard
Windscreen 2-Piece Flat Front	N/A
Door Entrance Position In	Front Overhang
Driver Door	Standard
OTHER SPECIFICATIONS	
Standard Exterior Colour – White	Standard
Sunvisor – Driver	Standard
Radio/CD, with USB Port, Speakers & Antennae	Optional (No USB Port)
Towbar & 50 mm Ball Hitch & 7-Pin Electrics	Optional
Lockers – Side in Wheelbase (Build to Order)	1 X 0.6 m ³ LHS, 2 X 0.6 m ³ RHS
Lockers – Rear Overhang (Build to Order)	2 X 0.4 m ³ , 1 X LHS & 1 X RHS
DIMENSIONS	
Wheelbase (mm)	6300
Overall Length (mm)	12356
Overall Height (mm)	3320
Overall Width (mm)	2523
Rear Overhang (mm)	3950
Front Overhang (mm)	2106
Ground Clearance in Wheelbase (mm)	410

MODEL	FVR
DESCRIPTION	65-SEATER
ANGLES	
Approach Angle (°)	12
Departure Angle (°)	10
MASS (kg)	
Tare – Front (Estimated)	4400
Tare – Rear (Estimated)	5850
Tare – Total (Estimated)	10250
V – Rating	17300
D/T – Rating	32000
A – Front	7100
A – Rear	10200
STANDARD EQUIPMENT	
Tools & Tool Box	Standard
Mudflaps on all Wheels	Standard
Spare Wheel, Carrier & Winch	Standard
Swing-Out Battery Box (2 X 12-V Batteries)	Standard
Lockable Slam-Type Passenger Door	Standard
Roof Vent / Escape Hatch	Standard
Emergency Exits – Windows & Roof Vent	Standard
2.5 kg Fire Extinguisher	Standard
Front Tow Hook	Standard
Front & Rear Bumper	Standard
Lockable Fuel Cap (Uses Ignition key)	Standard
Number Plate Holders (Front & Rear)	Standard
Exhaust Pipe Modified to Extend Beyond Body	Standard
Reverse Buzzer	Standard
WARRANTY & SERVICE	
Warranty – Chassis	2 Years / Unlimited km
Warranty – Bus Main Body (Integrity & Structure)	3 Years
Service Intervals (Standard Operation)	20 000 km
Defective Bus Component: Hinges, Locks, etc.	1 Year