

N-SERIES

*Specification
Sheet*

NQR
34-SEATER BUS

www.isuzu.co.za f 

ISUZU

With you, for the long run

| MODEL | NQR |
|---|---------------------|
| DESCRIPTION | 34-SEATER |
| ENGINE | |
| Engine & Exhaust Emission Level | 4HK1-TCN Euro 2 |
| Aspiration | Turbo & Intercooler |
| Injection System | Common Rail |
| Displacement (cm ³) | 5193 |
| Power @ r/min (kW) | 110 @ 2600 |
| Torque @ r/min (Nm) | 404 @ 1500 – 2600 |
| Transmission: Manual Synchromesh (NO AMT) | 6-Speed MYY6S |
| Clutch Diameter (mm) | 325 Single Plate |
| Axle Ratio : 1 | 5.125 |
| Auxiliary Brake | Exhaust |
| ABS | Standard |
| Electrical System (V) & 2 X 12-V Batteries | 24 |
| Tyre Size | 225 / 70 R19.5 |
| Fuel Tank Capacity (litres) | 100 |
| Coolant Level Sensor | N/A |
| BEAME Tracking Device – Mix Telematics 2017 | Standard |
| Road Speed (Max – Limited for Buses) | 100 |
| Gradeability % @ 'V' Mass, 1st Gear & Peak Torque | 31 |
| SEATING | |
| Driver | 1 |
| Passengers | 34 |
| Total | 35 |
| INTERIOR | |
| Individual Thin-Split Back Seat – Vinyl | Standard |
| Individual Thin-Split Back Seat – Printed Vinyl | Optional |
| Individual Thin-Split Back Seat – Dini Cloth | Optional |
| Basic Reclining Seats in Dini Cloth | Optional |
| Mechanical Suspension – Driver Seat | N/A |
| Air Suspension – Driver Seat | N/A |

| MODEL | NQR |
|--|---|
| DESCRIPTION | 34-SEATER |
| INTERIOR | |
| Lap Belts – All Seats | Standard |
| Blue GRP Floor & Up to Window Height | Standard |
| GRP with LED Strip-Lights in Roof | Standard |
| Heater & Demister (Driver) | Standard |
| Parcel Shelf – Vinyl or Perforated Steel | Optional |
| EXTERIOR | |
| Tinted Windows – Rubber-Mounted Sides Only | Standard |
| Tinted Bonded Side Windows | Optional |
| Windscreen 1-Piece Panoramic (Curved) | Standard |
| Windscreen 2-Piece Panoramic (Shaded Top) | N/A |
| Windscreen 2-Piece Flat Front | N/A |
| Door Entrance Position In | Wheelbase |
| Driver Door | Standard |
| OTHER SPECIFICATIONS | |
| Standard Exterior Colour – White | Standard |
| Sunvisor – Driver | Standard |
| Radio/CD, with USB Port, Speakers & Antennae | Optional |
| Towbar & 50 mm Ball Hitch & 7-Pin Electrics | Optional |
| Lockers – Side in Wheelbase (Build to Order) | 1 X 0.4 m ³ |
| Lockers – Rear Overhang (Build to Order) | 2 X 0.4 m ³ , 1 X LHS & 1 X RHS |
| DIMENSIONS | |
| Wheelbase (mm) | 4175 |
| Overall Length (mm) | 8358 |
| Overall Height (mm) | 2770 |
| Overall Width (mm) | 2240 |
| Rear Overhang (mm) | 2920 |
| Front Overhang (mm) | 1263 |
| Ground Clearance in Wheelbase (mm) | 400 |

| MODEL | NQR |
|--|------------------------|
| DESCRIPTION | 34-SEATER |
| ANGLES | |
| Approach Angle (°) | 18 |
| Departure Angle (°) | 11 |
| MASS (kg) | |
| Tare – Front (Estimated) | 2200 |
| Tare – Rear (Estimated) | 3100 |
| Tare – Total (Estimated) | 5300 |
| V – Rating | 8500 |
| D/T – Rating | 12000 |
| A – Front | 3100 |
| A – Rear | 6600 |
| STANDARD EQUIPMENT | |
| Tools & Tool Box | Standard |
| Mudflaps on all Wheels | Standard |
| Spare Wheel, Carrier & Winch | Standard |
| Swing-Out Battery Box (2 X 12-V Batteries) | Standard |
| Lockable Slam-Type Passenger Door | Standard |
| Roof Vent / Escape Hatch | Standard |
| Emergency Exits – Windows & Roof Vent | Standard |
| 2.5 kg Fire Extinguisher | Standard |
| Front Tow Hook | Standard |
| Front & Rear Bumper | Standard |
| Lockable Fuel Cap (Uses Ignition key) | Standard |
| Number Plate Holders (Front & Rear) | Standard |
| Exhaust Pipe Modified to Extend Beyond Body | Standard |
| Reverse Buzzer | Standard |
| WARRANTY & SERVICE | |
| Warranty – Chassis | 2 Years / Unlimited km |
| Warranty – Bus Main Body (Integrity & Structure) | 3 Years |
| Service Intervals (Standard Operation) | 20 000 km |
| Defective Bus Component: Hinges, Locks, etc. | 1 Year |